Weight	Weight: 36.00KGS(L) ; Weight, 38KGS	
Cover		
Absorber	Copper Sheet	Material, Low-iron Pattered Tempered Glass; Thickness, 3.2MM; Transmittance, 91%; Quantities, 1PCS.
Surface Treatment	Germany Blue Film	
Absorptivity	0.95～0.98	
Emissivity	0.03～0.06	
Solar Fins	140MMX0.4MM	
Header Tuber	Material, Copper, TP2; Diameter,22MM; Thickness, 0.6MM or Thickness 0.55MM(L); Length, 1060MM; Quantities, 2PCS.	
Riser Tuber	Material, Copper, TP2; Diameter,10MM; Thickness, 0.5MM or Thickness 0.45MM(L); Length, 1888MM; Quantities,7PCS;	
Construction	Fin & Tubes(Ultrasonic Welding); Working Pressure,0.6Mpa; Conductivity (W/mK):<= 0.048W/m.K under test temperature 70℃	
Insulation& Sealing Tape	Material, Fibre Glass; Density, Density ,16KG/CBM Back: 30MM /Side:35MM; EPDM Sealing Tape, Double or Single(L)	
Frame & Back Plate	6063 Aluminum Alloy;Sliver White;Thickness 0.85MM(L) or Thickness 1.00MM; ,; Galvanized Steel Back Plate; 0.3MM Thickness	